

IR Vari-focus bullet Network Camera

Product Type

IR Vari-focus bullet Network Camera

Product Model

BSR-IM2210-B0801



Key Features

- ✧ 1.3MP (1280×960) high resolution
- ✧ Smart video detection
- ✧ Smart focus
- ✧ Support 1-ch audio I/O, 1-ch alarm I/O(Optional)
- ✧ Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB(Optional)
- ✧ Analog Output(Optional)
- ✧ Up to 30m IR visibility
- ✧ True day/night
- ✧ 3D DNR & DWDR & BLC
- ✧ Impact Protection: IK10
- ✧ IP66 rating
- ✧ PoE

Specifications

| Parameters/Model | | BSR-IM2210-B0801 |
|------------------|-------------------|--------------------------------------|
| Camera | Image Sensor | 1/3" Progressive Scan CMOS |
| | Min. Illumination | 0.1Lux@(F1.2), AGC ON, 0 Lux with IR |
| | Shutter Time | 1/25s--1/10,000s |
| | Lens | 2.8-12mm@F1.4 |
| | Lens Mount | φ14 |

| Parameters/Model | | BSR-IM2210-B0801 |
|----------------------|--------------------------|---|
| | Auto Iris | DC Drive |
| | Digital Noise Reduction | 3D DNR |
| | Wide Dynamic Range | Digital WDR |
| | Day & Night | IR cut filter with auto switch |
| Compression Standard | Video Compression | H.264/MJPEG |
| | H.264 Codec Profile | Main Profile |
| | Bit Rate | 64Kbps—8Mbps |
| | Audio Compression | G.711/G.722.1/G.726/MP2L2(Optional) |
| | Triple Streams | Yes |
| Image | Max. Image Resolution | 1280×960 |
| | Frame Rate | 30fps(1280×960) 25fps(1280×720) |
| | Image Settings | Saturation, brightness, contrast, sharpness adjustable through client software or browser |
| | BLC | Yes, zone configurable |
| | Video Active Enhancement | Yes |
| Network | Alarm Trigger | Motion detection, abnormality alarm, video block alarm |
| | Protocols | TCP/IP , RTP , UDP , HTTP , DHCP , DDNS , PPPoE , NTP |
| | System Compatibility | ONVIF |
| Interface | Communication Interface | 1 RJ45 10M/100M Ethernet Interface |
| | On-board storage | Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB |
| General | Operation Conditions | -10°--55°; humidity 95% or less |
| | Power Supply | 12VDC ±10% ; PoE(802.3af) |
| | Power Consumption | Max.5W |
| | Impact Protection | IK 10 |
| | Ingress Protection | IP66 |
| | IR Range | 30m |
| | Dimensions | 147(Φ)mm*123mm(H) |
| | Weight | 1200g |

Typical Applications

Suitable for financial, military, prisons, airports, factories, government, hotels, such as IP monitoring, especially suitable for the night, such as outdoor, warehouses and other locale with auxiliary infrared light source.

Picture



Dimensions

