

Panoramic Network Camera

Product Type

Panoramic Network Camera

Product Model

BSR-IPH520-W



Key Features

- ✧ 2Mp(1920*1080) high resolution
- ✧ 2Mp Panoramic fisheye lens, angle of view up to 185°
- ✧ 360° /180° panoramic mode
- ✧ 360° auto cruise and preset cruise
- ✧ 120dB WDR
- ✧ External POE

Specifications

Parameters/Model		BSR-IPH520-W
Camera	Sensor	1/2.8" CMOS
	Minimum Illumination	0.1Lux(F1.2) , IR On 0.01Lux(F1.2)
	Electronic shutter	1/2s--1/10,000s
	Lens Mount	M12
	Lens	1.19mm , F2.0, angle of view 185°
	Auto Iris	Fixed
	AGC	Auto
	BLC	Auto/Manual
	WDR	120dB WDR
	BLC	Yes
	HLC	Yes

Parameters/Model		BSR-IPH520-W
	3D DNR	Yes
Compression	Video Compression	H.264/MPEG4/MJPEG/JPEG
	Audio Compression	G.711/G.726
	Code Rate	64Kbps ~ 8Mbps
Image	Resolution	1920×1080
	Frame Rate	30/25fps (1920×1080/ 1920×1024 /1600×1200/ 1280×1024 /1280×960/1280×720)
	Image Setting	Saturation, brightness and contrast ratio be adjusted by CMS or IE
General Function	Alarm Trigger	Motion detection, abnormality alarm, video block alarm and etc.
	Alarm Linkage Output	Yes
	Protocol	TCP/IP , RTP , UDP , HTTP , DHCP , DDNS , PPPoE , NTP and etc.
	Screenshot	Yes
	VAE	Yes
	Multi Stream	Triple Stream
Interface	Network	1 RJ45 10M/100M self-adaptive Ethernet interface
General	Power	DC12V
	Consumption	≤5.0W
	Temperature	- 10°C ~ + 55°C
	Humidity	< 90%
	Dimensions	119mm(Φ)×72mm *(H)
	Weight	800g

Typical Applications

Suitable for financial, military, prisons, airports, factories, government, hotels, such as IP monitoring, especially suitable for the night, such as outdoor, warehouses and other locale with auxiliary infrared light source.

Picture



Dimensions

