

Network Video Recorder BSR-NR2208HS-T Series

Product Model:

BSR-NR2208HS-T

Key Features

- ✧ 8-Ch IP Cameras input
- ✧ Third-party network cameras supported
- ✧ HDMI and VGA output up to 1920X1080 resolution
- ✧ Up to 5MP resolution recording
- ✧ 8 independent network interfaces for built-in switch
- ✧ Dual stream playback
- ✧ HDD quota and group management

Specifications

Parameter/Model	BSR-NR2208HS-T
Video/Audio Input	
Video Input	8-Ch
Audio Input	No("A" series: 1-Ch input)
Network	
Incoming Bandwidth	80Mbps
Outgoing Bandwidth	10Mbps
Video/Audio Output	
Live View/Playback	5MP / 3MP / 1080P / 720P / VGA / 4CIF / DCIF / 2CIF/ CIF / QCIF
Capability	18-Ch@D1; 6-Ch@720P; 3-Ch@1080P
Frame Rate	PAL: 1-25fps, NTSC:1-30fps
HDMI/VGA Output	1-Ch resolution: 1024x768/1280x720/1280x1024/1366x768/1440x900/1920x1080
Audio Output	No("A" series :1-Ch out)
Synchronous Playback	8-Ch
Dual Stream	Support
Hard Disk	
SATA	2 SATA interface for 1HDD
Capability	Up to 4TB for each disk
External Interface	
Network Interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface

Parameter/Model	BSR-NR2208HS-T
Built-in Switch	8 independent 10 /100 Mbps Ethernet interfaces
USB Interface	2*USB 2.0
Alarm In/out	No("M" series: 4-Ch in; 1-Ch out)
General	
Power Supply	DC 12V 2A
Consumption	≤10W(Without hard disk)
Working Temperature	-10℃--40℃
Working Humidity	10%--90%
Dimensions(W*D*H)	322*255*46(mm)
Weight	1.6Kg(Without hard disk)

Typical Applications

Applies to high request for image quality monitoring sites such as solution for bank counter, also suitable for city traffic, shopping mall, supermarket, hotel, airport and station, etc.

Front Panel



Rear Panel



- ① Video Out
- ② VGA Interface
- ③ HDMI Interface
- ④ USB Interface
- ⑤ RS-485 Interface
- ⑥ LAN Interface
- ⑦ Network Interface with PoE function
- ⑧ Power Supply
- ⑨ Power Switch