

Network Video Recorder BSR-NR2100HS-T Series

Product Model:

BSR-NR2104HS-T BSR-NR2108HS-T

Key Features

- ✧ Up to 8-Ch IP Cameras input
- ✧ Third-party network cameras supported
- ✧ HDMI and VGA output up to 1920X1080 resolution
- ✧ Up to 5MP resolution recording
- ✧ 4/8 independent network interfaces for built-in switch
- ✧ Dual stream playback
- ✧ HDD quota and group management

Specifications

Parameter/Model	BSR-NR2104HS-T	BSR-NR2108HS-T
Video/Audio Input		
Video Input	4-Ch	8-Ch
Audio Input	No("A" series: 1-Ch input)	
Network		
Incoming Bandwidth	40Mbps	80Mbps
Outgoing Bandwidth	50Mbps	10Mbps
Video/Audio Output		
Live View/ Playback	5MP / 3MP / 1080P / 720P / VGA / 4CIF / DCIF / 2CIF/ CIF / QCIF	
Capability	8-Ch@D1; 2-Ch@720P; 1-Ch@1080P	18-Ch@D1; 6-Ch@720P; 3-Ch@1080P
Frame Rate	PAL: 1-25fps, NTSC:1-30fps	
HDMI/VGA Output	1-Ch resolution: 1024x768/1280x720/1280x1024/1366x768/1440x900/1 920x1080	
Audio Output	No("A" series :1-Ch out)	
Synchronous Playback	4-Ch	8-Ch
Dual Stream	Support	
Hard Disk		
SATA	1 SATA interface for 1HDD	
Capability	Up to 4TB for each disk	

Parameter/Model	BSR-NR2104HS-T	BSR-NR2108HS-T
External Interface		
Network Interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface	
Built-in Switch	4 independent 10 /100 Mbps Ethernet interfaces	8 independent 10 /100 Mbps Ethernet interfaces
USB Interface	2*USB 2.0	
Alarm In/out	No("M" series: 4-Ch in; 1-Ch out)	
General		
Power Supply	DC 12V 2A	
Consumption	≤10W(Without hard disk)	
Working Temperature	-10°C--40°C	
Working Humidity	10%--90%	
Dimensions(W*D*H)	270*255*46(mm)	322*255*46(mm)
Weight	1.6Kg(Without hard disk)	

Typical Applications

Applies to high request for image quality monitoring sites such as solution for bank counter, also suitable for city traffic, shopping mall, supermarket, hotel, airport and station, etc.

Front Panel



Rear Panel



- ① Video Out
- ② VGA Interface
- ③ HDMI Interface
- ④ USB Interface
- ⑤ RS-485 Interface
- ⑥ LAN Interface
- ⑦ Network Interface with Built-in Switch
- ⑧ Power Supply
- ⑨ Power Switch