

Network Video Recorder BSR-NR2200HS Series

Product Model

BSR-NR2208HS BSR-NR2216HS BSR-NR2224HS

Key Features

- ✧ Up to 24-Ch IP Cameras input
- ✧ Third-party network cameras supported
- ✧ HDMI and VGA output up to 1920X1080 resolution
- ✧ Up to 5MP resolution recording
- ✧ Dual stream playback
- ✧ HDD quota and group management

Specifications

Parameters/Model	BSR-2208HS	BSR-22016HS	BSR-2224HS
Video/Audio Input			
Video Input	8-Ch	16-Ch	24-Ch
Audio Input	No	1-Ch RCA	
Network			
Incoming Bandwidth	80 Mbps	120 Mbps	180 Mbps
Outgoing Bandwidth	10 Mbps	80 Mbps	80 Mbps
Video/Audio Output			
Live view / Playback	5MP / 3MP / 1080P / 720P / VGA / 4CIF / DCIF / 2CIF/ CIF / QCIF		
Capability	8-Ch@D1; 2-Ch@720P; 1-Ch@1080P	35-Ch@D1; 8-Ch@720P; 4-Ch@1080P	35-Ch@D1; 8-Ch@720P; 4-Ch@1080P
Frame Rate	PAL: 1-25fps, NTSC:1-30fps		
HDMI/VGA Output	1-Ch resolution: 1024x768/1280x720/1280x1024/1366x768/1440x900/1920x1080		
Audio Output	No	1-Ch RCA	
Synchronous Playback	8-Ch	16-Ch	24-Ch
Dual Stream	Support		
Hard Disk			
SATA	1 SATA interface for 1HDD	2 SATA interface for 2HDD	
Capability	Up to 4TB for each disk		
External Interface			

Parameters/Model	BSR-2208HS	BSR-22016HS	BSR-2224HS
Network Interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface		
USB Interface	2*USB 2.0		
Alarm In/out	No		
General			
Power Supply	DC12V 3A		
Consumption	≤10W(Without hard disk)		
Working Temperature	-10℃--40℃		
Working Humidity	10%--90%		
Dimensions(W*D*H)	322*255*46(mm)	376*278*46(mm)	376*278*46(mm)
Weight	1.6Kg(Without Hard disk)	1.6Kg(Without Hard disk)	

Typical Applications

Applies to high request for image quality monitoring sites such as solution for bank counter, also suitable for city traffic, shopping mall, supermarket, hotel, airport and station, etc.

Front Panel



Rear Panel



- ① LAN Interface
- ② VGA Interface
- ③ Audio In
- ④ Audio Out
- ⑤ HDMI Interface
- ⑥ USB Interface
- ⑦ Power Supply