

Network Video Recorder BSR-NR2200HS-H Series

Product Model:

BSR-NR2216HS-H BSR-NR2224HS-H BSR-NR2232HS-H

Key Features

- ✧ Up to 32-Ch IP Cameras input
- ✧ Third-party network cameras supported
- ✧ HDMI and VGA output up to 1920X1080 resolution
- ✧ Up to 5MP resolution recording
- ✧ Dual stream playback
- ✧ 4 SATA HDD interface up to 4TB each
- ✧ HDD quota and group management

Specifications

Parameter/Model	BSR-NR2216HS-H	BSR-NR2224HS-H	BSR-NR2232HS-H
Video/Audio Input			
Video Input	16-Ch	24-Ch	32-Ch
Audio Input	1-Ch RCA		
Network			
Incoming Bandwidth	120Mbps	180 Mbps	220 Mbps
Outgoing Bandwidth	80Mbps	80 Mbps	80 Mbps
Video/Audio Output			
Decoding resolution	5MP / 3MP / 1080P / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF		
Capability	35-Ch@D1; 8-Ch@720P; 4-Ch@1080P	35-Ch@D1; 8-Ch@720P; 4-Ch@1080P	35-Ch@D1; 8-Ch@720P; 4-Ch@1080P
Frame Rate	PAL: 1-25fps, NTSC:1-30fps		
HDMI/VGA Output	1-Ch resolution: 1024x768/1280x720/1280x1024/1366x768/1440x900/1920x1080		
Audio Output	1-Ch, RCA		
Synchronous Playback	16-Ch	24-Ch	32-Ch
Dual Stream	Support		
Hard Disk			
SATA	4 SATA interfaces for 4 HDD		
Capability	Up to 4TB for each disk		

Parameter/Model	BSR-NR2216HS-H	BSR-NR2224HS-H	BSR-NR2232HS-H
External Interface			
Network Interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface		
USB Interface	2*USB 2.0		
Alarm In/out	No ("M" series support 4-Ch in, 1-Ch out)		
General			
Power Supply	DC12V 6A		
Consumption			
Working Temperature	-10°C--40°C		
Working Humidity	10%--90%		
Dimensions(W*D*H)	423*325*70(mm)		
Weight	3.7Kg(Without hard disk)		

Typical Applications

Applies to high request for image quality monitoring sites such as solution for bank counter, also suitable for city traffic, shopping mall, supermarket, hotel, airport and station, etc.

Front Panel



Rear Panel



- | | |
|-----------------|------------------|
| ① LAN Interface | ⑤ HDMI Interface |
| ② VGA Interface | ⑥ USB Interface |
| ③ Audio In | ⑦ Power Switch |
| ④ Audio Out | ⑧ Power Supply |