

Hybrid Video Recorder BSR-HR7100N Series

Product Model:

BSR-HR7104N BSR-HR7108N BSR-HR7116N

Key Features

- ✧ H.264 Video Compression
- ✧ Third-party network cameras supported
- ✧ HDMI and VGA output up to 1920X1080 resolution
- ✧ Up to 5MP resolution recording
- ✧ 8 SATA HDD interface up to 4TB each
- ✧ Dual stream playback
- ✧ HDD quota and group management

Specifications

Parameter/Model	BSR-HR7104N	BSR-HR7108N	BSR-HR7116N
Video/Audio Input			
Analog Input	4-Ch	8-Ch	16-Ch
IP Input	4-8 Ch	8-16 Ch	4-32 Ch
Audio Input	4- Ch	8-Ch	16-Ch
Video/Audio Output			
Live View/ Playback	5MP / 3MP / 1080P / 720P / VGA / 4CIF / DCIF / 2CIF/ CIF / QCIF		
Frame Rate	PAL: 1-25fps, NTSC:1-30fps		
HDMI/VGA Output	1-Ch resolution: 1024x768/1280x720/1280x1024/1366x768/1440x900/1920x1080		
CVBS Output	1-ch, BNC(1.0Vp-p, 75Ω) Resolution: 704x576(PAL); 704x480(NTSC)		
Audio Output	1-Ch BNC; 1-Ch HDMI		
Synchronous Playback	Up to 8-Ch	Up to 16-Ch	Up to 16-Ch
Dual Stream	Support		
Hard Disk			
SATA	8 SATA interfaces for 8 HDDS		
Capability	Up to 4TB for each disk		
External Interface			
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface		

Parameter/Model	BSR-HR7104N	BSR-HR7108N	BSR-HR7116N
USB Interface	3*USB 2.0		
PTZ Control	2 RS485		
Communication	1 RS232		
Alarm In/out	6-Ch input/2-Ch output	16-Ch input/4-Ch output	16-Ch input/4-Ch output
Video Intercom	1-Ch BNC in; 1-Ch BNC out		
General			
Power Supply	100-240V		
Consumption	≤31W(Without hard disk)		
Working Temperature	-10℃-- 55℃		
Working Humidity	10%--90%		
Dimensions(W*D*H)	440*425*88(mm) 2U Chassis		
Weight	7Kg(Without hard disk)		

Typical Applications

Applies to high request for image quality monitoring sites such as solution for bank counter, also suitable for city traffic, shopping mall, supermarket, hotel, airport and station, etc.

Picture

