

## Digital Video Recorder BSR-2100AS Series

### Product Model:

BSR-2104AS-F BSR-2108AS-H BSR-2116AS-H

### Key Features

- ✧ H.264 video compression
- ✧ Up to 16-Ch video input
- ✧ WD1 resolution real time recording
- ✧ HDMI/VGA/BNC output at 1920\*1080P resolution
- ✧ Up to 16-Ch synchronous playback
- ✧ HDD quota and group management

### Specifications

Parameter/Model	BSR-2104AS-F	BSR-2108AS-H	BSR-2116AS-H
Video/Audio Input			
Video Input	4-Ch	8-Ch	16-Ch
Audio Input	2-Ch RCA		
Video/Audio Output			
Recording resolution	960H/D1:100fps(PAL) 120fps(NTSC)	960H/D1:200fps(PAL) 240fps(NTSC)	960H/D1:400fps(PAL) 480fps(NTSC)
Video Output	1-Ch BNC; 1-Ch VGA; 1-Ch HDMI		
Audio Output	1-Ch, RCA		
Synchronous Playback	4-Ch 960H	8-Ch 960H	16-Ch 960H
Dual Stream	Support		
Hard Disk			
SATA	1 SATA interfaces for 1 HDD	2 SATA interfaces for 2 HDD	
Capability	Up to 4TB for each disk		
External Interface			
Network Interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface		
PTZ	1 RS485		
USB Interface	2*USB 2.0		
General			
Power Supply	DC12V 3A	DC12V 3.5A	
Consumption	≤10W(Without hard disk)		
Working Temperature	-10℃--40℃		

Parameter/Model	BSR-2104AS-F	BSR-2108AS-H	BSR-2116AS-H
Working Humidity	10%--90%		
Dimensions(W*D*H)	270*215*46(mm)	322*255*46(mm)	376*276*48(mm)
Weight	1.6Kg(Without hard disk)		

### Typical Applications

Applies to high request for image quality monitoring sites such as solution for bank counter, also suitable for city traffic, shopping mall, supermarket, hotel, airport and station, etc.

### Picture



### Rear Panel



- ① Video In
- ② Video Out
- ③ Audio In
- ④ Audio Out
- ⑤ VGA Interface
- ⑥ HDMI Interface
- ⑦ LAN Interface
- ⑧ USB Interface
- ⑨ RS-485 Interface
- ⑩ Power Supply